
RAK16-POE-A



- 19`` patch panel surge protector for POE-B
- 32 ports
- In/Out front : RJ45
- Maintenance possible per port
- Secondary Protection
- UL497B

Características eléctricas		
Perdida de inserción		< 1 dB
Corriente máx. De línea	IL	750 mA
Capacidad máx.	C	< 25 pF (ligne ethernet)
Capacity	pF	<25
Telecom Discharge Current	kA	0,05
Telecom Total Discharge Current	kA	0,05
Telecom Discharge Current	kA	0,05
Telecom Discharge Current	kA	0,05
Max Discharge Current	kA	0.0500
Instalación		
Operating Temperature	°C	-40.0000
Operating Temperature	°C	85.0000
Operating Temperature	°F	-40.0000
Operating Temperature	°F	85.0000
Operating Relative Humidity	%RH	95
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		aluminum
Mounting		Rack mount
IP Environmental rating		IP20
Installation Location		indoor
Product Dimension	mm	483.0000
Product Dimension	mm	88.0000
Product Dimension	In	19.0200
Product Dimension	In	3.4650
Miscelánea		
Individual Pack		Yes
Storage Temperature	°C	-40.0000
Storage Temperature	°C	85.0000
Storage Temperature	°F	-40.0000
Storage Temperature	°F	85.0000
Instalación		
Cable type		Ethernet
Código		
6372		